

### FEATURES

- GBC was designed with solid lead plated and gelled electrolyte technology.
- A deep-cycle lead-acid battery is designed to deliver a maximum capacity and cycles as discharging.
- High temperature stability, mechanical strength and low acid displacement.
- Superior performance with deep discharges.
- Patented safety valve to have accurate pressure operating for long battery life.

### APPLICATION

- Golf Cars
- Power Wheelchairs
- Floor Sweepers
- Recreational Vehicle (RV)
- Renewable Energy



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	105 Ah @ 5 hour rate F.V.(1.70V/cell)
Approx. Weight	39500g(87.08lbs.)
Terminals	I2
Internal Resistance	≤5mΩ (Fully Charged )
Max. Discharge Current	800 A (5 sec.)
Max. Charge Current	30.0 A
Self Discharge	< 2% per month (25°C)
Operating Temperature Range	-20°C~55°C(-4°F~131°F)
Container Material	ABS(UL94-HB, UL94-V0 is optional)

ISO 9001	
ISO14001	
UL	
CE	
● GB/T 7403.1-2008	
● IEC60254-1: 2005	

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ Length 344±2.0 (13.54±0.08)</li> <li>■ Width 172±2.0 (6.77±0.08)</li> <li>■ Container Height 263.8±2.0 (10.39±0.08)</li> <li>■ Total Height 280.3±2.0 (11.04±0.08)</li> </ul>		<ul style="list-style-type: none"> <li>● Terminal I2</li> </ul> <p>[M6 BOLT]</p> <p>Terminal Hardware Initial Torque: 5.5Nm±5%</p>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

Discharge Time	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
F.V. (V/cell) 1.80V	1334	842	354.7	246.1	138.0	71.92
1.75V	1354	864	360.0	249.8	140.9	71.95
1.70V	1364	882	363.9	252.0	142.0	73.53
1.65V	1369	891	367.5	253.0	142.7	73.68
1.60V	1369	899	369.4	253.6	142.7	73.68

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

Discharge Time	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
F.V. (V/cell) 1.80V	111.2	70.2	29.56	20.51	11.50	5.993
1.75V	112.8	72.0	30.00	20.82	11.74	5.996
1.70V	113.7	73.5	30.32	21.00	11.84	6.128
1.65V	114.1	74.2	30.63	21.08	11.89	6.140
1.60V	114.1	74.9	30.78	21.14	11.89	6.140

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.