



VRLA Rechargeable Battery

HRL22-12 (HRL22-12FR)

FEATURES

- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for high rate usage
- Long life expectancy up to 10 years in float application
- Absorbent Glass Mat technology for efficient gas recombination
- The power density at 5 min~15min discharging rate is 30% higher than BP series

APPLICATION

- UPS
- Emergency Lights
- Medical Equipments
- Wind Power
- Lawn Mowers
- Jump Starter
- Booster
- Video Camcorders(VCR)

SPECIFICATIONS

Nominal Voltage	12V	
Nominal Capacity	10 Hour Rate (2000mA, 10.5V)	20.0 Ah
	15 Min Rate (528W, 7.8V)	11.0 Ah
Approx. Weight	6500g(14.33lbs.)	
Terminals	B1 (Fitting M5 bolt & nut) , T2 and I1 are optional	
Max. Discharge Current	300 A (5 sec.)	
Max. Charge Current	6.0 A	
Operating Temperature Range	Charge	0°C~40°C(32°F~104°F)
	Discharge	-20°C~50°C(-4°F~122°F)
	Storage	-20°C~40°C(-4°F~104°F)
Self Discharge	< 3% per month (25°C)	
Internal Resistance	≤ 9mΩ (Fully Charged)	



CONTAINER MATERIAL

- HRL22-12:
ABS: UL 94-HB (Dark gray color)
- HRL22-12FR:
ABS: UL 94-V0 (Light gray color)

ISO 9001


ISO14001

C4M20310-2474-E-16


CE

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

OUTER DIMENSIONS mm(inch)	Length (L)	Width (W)	Container Height (H)	Total Height (TH)
		181±1.5(7.13±0.06)	76±1.5(2.99±0.06)	166±1.5(6.54±0.06)




TERMINAL TYPE




Terminal Hardware Initial Torque:
B1(2.5Nm±5%),I1(4.0Nm±5%)

HRL22-12 (HRL22-12FR) discharge characteristics (25°C /77°F)




Battery Charging Characteristics



Charging Procedure

Application	Charging method	Charging Voltage at 25°C (V/cell)	Temperature compensation coefficient of charging voltage (mV/°C /cell)	Max. charging current (CA)	Charging time 0.1CA, 25°C (h)		Temp (°C)
					100% discharge	50% discharge	
For standby power Source	Constant voltage & Constant current charging (with current restriction)	2.25~2.30	-3	0.3	24	20	0~40 (32~104°F)
For cycle service					16	10	

Effect Of Temperature On Long Term Float Life



Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V	902.0	616.0	446.1	380.6	289.3	220.0	183.7	161.7	89.2
1.70V	1078.0	687.5	485.1	403.2	301.4	228.3	189.8	165.6	90.9
1.60V	1155.0	723.3	507.1	418.0	308.0	233.8	193.6	168.3	92.4
1.50V	1188.0	737.0	518.1	424.6	311.9	236.5	195.8	170.0	92.9
1.40V	1210.0	746.9	524.2	428.5	314.1	238.2	197.5	171.1	93.1
1.30V	1221.0	753.5	528.0	431.2	315.7	239.3	198.6	171.6	93.4

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	20 Min	30 Min	40 Min	50 Min	60 Min	120 Min
1.80V	80.54	54.04	38.59	32.64	24.52	18.50	15.37	13.48	7.43
1.70V	98.00	60.31	41.96	34.58	25.54	19.20	15.88	13.80	7.58
1.60V	105.00	63.45	43.87	35.85	26.10	19.66	16.20	14.03	7.70
1.50V	108.00	64.65	44.82	36.42	26.43	19.89	16.38	14.17	7.74
1.40V	110.00	65.52	45.35	36.75	26.62	20.03	16.53	14.26	7.76
1.30V	111.00	66.10	45.67	36.98	26.75	20.13	16.62	14.30	7.78

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained herein.

Trials A/0 REV. Dec. 2010

USA:
B&B BATTERY(USA) INC.
6415 RANDOLPH ST.COMMERCE, CA,90040 U.S.A.
TEL:1-323-278-1900.1-800-278-8599
FAX:1-323-278-1268
E-Mail:sales@bb-battery.com

CHINA FACTORY:
B. B. BATTERY CO., LTD.
CHENG DONG TRIAL AREA,HUANG GANG,
RAOPING, GUANG DONG,CHINA,515700
TEL:86-768-7601001-2
FAX:86-768-7601469
E-Mail:maggy@bb-battery.com

EUROPE:
B&B BATTERY(EUROPE) B.V.
SUITE 8, HAAKSBERGWEG 33, 1101
BP AMSTERDAM, THE NETHERLANDS
TEL: 31-30-3200190
MOBILE: 886-933896989
E-Mail: gary@bb-battery.com

HONG KONG:
B&B BATTERY(Hong Kong) Co.
TEL:852-2311-4918
FAX:852-2739-1182
E-Mail:bbhk@hkstar.com

JAPAN:
B&B BATTERY(JAPAN) CO., LTD.
1375-11 NARAHARA-MACHI,HACHIOJI,
TOKYO 193-0803,JAPAN.
TEL:81-426-25-6375
FAX:81-426-25-6375
E-Mail:miyata@bb-battery.com

TAIWAN:
B. B. BATTERY(TAIWAN) CO., LTD.
TEL:886-6-502-5150
FAX:886-6-589-8087
E-Mail:kevin@bb-battery.com