

## FEATURES

- GBS delivers long cycle life and prolong life in elevated ambient temperatures.
- The generated heat can easily flow to the case walls because the whole volume of the cell is filled with gel.
- The immobilization of the electrolyte in the gel makes acid stratification impossible.
- Maintenance free (no water topping-up required).
- Low self-discharge rate, lower than 2% capacity loss per month.
- A small distribution of the special valve opening and closing pressure is important for a good (cycle) life time of the battery.

## APPLICATION

- Solar power stations
- Telecommunications installations
- Traffic lights
- Street lightening
- Wind power

## SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	85Ah @ 100 hour rate F.V.(1.80V/cell)
Approx. Weight	28500g(62.83lbs.)
Terminals	I2
Internal Resistance	≤6mΩ (Fully Charged)
Max. Discharge Current	700 A (5 sec.)
Max. Charge Current	16.0 A
Operating Temperature Range	-20°C~55°C(-4°F~131°F)
Container Material	ABS(UL94-HB UL94-V0 is optional)



ISO 9001	
ISO 14001	
UL	
CE	
<ul style="list-style-type: none"> <li>● IEC 61427-2005</li> <li>● GB/T 22473-2008</li> </ul>	

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ Length 329.0±2 (12.95±0.08)</li> <li>■ Width 172.0±2 (6.77±0.08)</li> <li>■ Container Height 214.5±2 (8.44±0.08)</li> <li>■ Total Height 219±2 (8.60±0.08)</li> </ul>		<ul style="list-style-type: none"> <li>● Terminal I2</li> </ul> <p>[M6 BOLT]</p> <p>Terminal Hardware Initial Torque: I2(5.5Nm±5%)</p>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	100 Hr	120 Hr
1.85V	540	236	163.5	87.8	46.61	10.20	8.52
1.80V	558	241	166.3	88.9	47.72	10.24	8.54
1.75V	563	245	168.1	90.2	48.13	10.31	8.61
1.70V	576	246	168.5	90.6	48.29	10.35	8.64
1.65V	578	246	169.0	90.8	48.40	10.40	8.66

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr	100 Hr	120 Hr
1.85V	45.5	19.83	13.62	7.34	3.98	0.845	0.711
1.80V	46.2	19.94	13.81	7.45	4.00	0.850	0.713
1.75V	47.4	20.26	13.94	7.54	4.03	0.856	0.715
1.70V	48.2	20.45	14.05	7.58	4.05	0.859	0.716
1.65V	48.4	20.59	14.12	7.62	4.06	0.862	0.718

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained herein.