

## VRLA Rechargeable Battery

# UPS12360XW

Standard Type

### FEATURES

- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed with very lower resistance and exceeding high power performance.
- Flame-arrestor is installed to ensure safety
- Absorbent Glass Mat technology for efficient gas recombination

### APPLICATION

- UPS
- Cable TV
- Golf-Carts
- Telecom
- Power station
- Marine




### SPECIFICATIONS


Nominal Voltage	12V
Nominal Capacity	360W @ 15 min-rate to 1.60V per cell @ 25°C(77°F)
Approx. Weight	26.4Kg(58.2lbs.)
Terminals	I2, B5 (Fitting M6 bolt & nut) is optional
Max. Charge Current	25.8 A
Short Circuit Current	2300 A
Operating Temperature Range	Charge 0°C~50°C(32°F~122°F)
	Discharge -20°C~60°C(-4°F~140°F)
	Storage -20°C~50°C(-4°F~122°F)
Self Discharge	< 3% per month (25°C)
Internal Resistance	≤ 4mΩ (Fully Charged )

### CONTAINER MATERIAL


- Standard: PP( UL 94-HB)  
Model Name: UPS12360XW
- Optional: Flame Retardant PP(UL 94-V0)  
Model Name: UPS12360XWFR




OUTER DIMENSIONS mm(inch)	Length (L)	Width (W)	Container Height (H)	Total Height (TH)
	261±2.0(10.28±0.08)	173±2.0(6.81±0.08)	200±2.0(7.87±0.08)	B5: 224±2.0(8.82±0.08) I2: 207±2.0(8.15±0.08)



## UPS12360XW(UPS12360XWFR) Charging Characteristics



## Battery Charging Characteristics



## Charging Procedure

Application	Charging method	Charging Voltage at 25°C (V/cell)	Temperature compensation coefficient of charging voltage (mV/°C/cell)	Max. charging current (CA)	Charging time 0.1CA, 25°C (h)		Temp (°C)
					100% discharge	50% discharge	
For standby power Source	Constant voltage & Constant current charging (with current restriction)	2.25~2.30	-3	0.3	24	20	0~50 (32~122°F)
For cycle service		2.40~2.50	-4	0.3	16	10	

## Constant power discharge characteristics at 25 °C/77 °F Unit: W

Discharge F.V. / Time	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
10.8V	3048	2240	1901	1554	1348	1183	950	800	692	492
10.5V	3416	2402	2012	1615	1389	1214	971	817	704	501
10.2V	3643	2505	2081	1656	1416	1233	986	827	713	506
9.9V	3795	2583	2128	1689	1438	1247	998	835	719	510
9.6V	3904	2630	2160	1712	1456	1260	1008	842	725	514

## Constant current discharge characteristics at 25 °C/77 °F Unit: A

Discharge F.V. / Time	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
10.8V	284	197	165	133	113	99	79	67.1	58.2	41.5
10.5V	311	212	174	138	119	102	81	68.2	59.2	42.1
10.2V	331	221	180	142	122	104	82	69.3	59.8	42.6
9.9V	344	228	185	145	123	105	83	70.4	60.4	42.9
9.6V	355	232	188	147	124	107	85	70.4	60.8	43.2

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.

For operation, please refer to the instruction from technical manual.

SC(for akku) Trial A/0 REV. Mar 2017

**USA:**  
 B&B BATTERY(USA) INC.  
 6415 RANDOLPH ST.COMMERCE, CA,90040 U.S.A.  
 TEL:1-323-278-1900.1-800-278-8599  
 FAX:1-323-278-1268  
 E-Mail:sales@bb-battery.com

**CHINA FACTORY:**  
 B.B. TECH(CHANGSHA) CO., LTD.  
 No.57 Dongsiroad, Changsha National Economic & Technical Development Zone, Changsha, Hunan PRC  
 TEL:86-731-82955888  
 FAX:86-731-82955111  
 E-Mail:maggy@bb-battery.com

**EUROPE:**  
 B&B BATTERY(EUROPE) B.V.  
 SUITE 8, HAAKSBERGWEG 33, 1101  
 BP AMSTERDAM, THE NETHERLANDS  
 TEL: 31-30-320-0190  
 MOBILE: 852-9128-2711  
 E-Mail: dliu@bb-battery.com

**HONG KONG:**  
 B&B BATTERY(Hong Kong) Co.  
 TEL:852-2311-4918  
 FAX:852-2739-1182  
 E-Mail:bbhk@hkstar.com

**JAPAN:**  
 B&B BATTERY(JAPAN) CO., LTD.  
 1375-11 NARAHARA-MACHI,HACHIOJI,  
 TOKYO 193-0803,JAPAN.  
 TEL:81-426-25-6375  
 FAX:81-426-25-6375  
 E-Mail:miyata@bb-battery.com

**TAIWAN:**  
 B.B. BATTERY(TAIWAN) CO., LTD.  
 TEL:886-6-502-5150  
 FAX:886-6-589-8087  
 E-Mail:kevinlin@bb-battery.com